

V19

19" SXGA Industrial Monitor with Resistive Touchscreen, Direct VGA



Features

- * 19" SXGA TFT LCD
- * Direct VGA video input interface
- * Flat-sealed front panel
- * Resistive Touchscreen (optional)
- * RS232 or USB interface for touchscreen function
- * Support industrial 10 ~ 30 Vdc power input (optional)
- * Easy wall and VESA arm mounting system
- * Front panel is IP65 compliant

Specifications

General

- **Button Controls** OSD control pad on rear side
- **Certification** CE
- **Enclosure** Front panel: Aluminium and flat-sealed
Rear cover: Anti-rust coating
- **Mounting** Panel, Wall, VESA arm or 19" rackmount
- **USB** Front USB access for extension (optional)
- **Video Port** VGA

LCD Display

- **Size /Type** 19" TFT Colour LCD
- **Max. Resolution** 1280 x 1024
- **Max. Colors** 16.7 M
- **Viewing Angle** 160°
- **Luminance** 300 cd/m²
- **Back Light** CFL

Power Supply

- **Power Requirement:** max. 2.5A a 12V
- **Power Input:** 2.5 Jack
- **Input Voltage:**
 - ▶ 12 Vdc
 - ▶ or 100 ~ 240 Vac (optional)
 - ▶ or 10 ~ 30 Vdc (optional)

Touchscreen (optional)

- **Controller:** EETI E-GALAX
- **Type:** 5-wire Resistive
- **Interface:** RS-232 or USB
- **Power Consumption:** +5 V @ 100 mA

Environmental

- **Operating Temp.:** 0 to 50° C
- **Storage Temp.:** - 20 to 60° C
- **Storage Humidity:** 10 to 90 % non condensing
- **Vibration:** 5 to 500 Hz, 1 Grms
- **Front Panel protection:** meet NEMA 4 & IP65

Mechanical

- **Construction:**
 - ▶ **Back:** Heavy-duty galvanized metal chassis
 - ▶ **Front:** Non-scratch black paint on aluminium frame
- **Wall fixing:** by 4 clamps
- **Weight:** 7 Kg
- **Dimension (W x H x D) :** 440 x 388 x 45 mm

